

VORT HR 350 AVEL



.æŠ-“ń¥ß-“ÛÎ|

Absorbed Current max (A)	1,4	Delivery max (l/s)	100
Absorbed Power max (W)	165	Delivery max (m³/h)	350
Filter class	F5	Pressure max (mmH2O)	90
Frequency (Hz)	50	Pressure max (Pa)	880
Insulation Class	I °	Sound power level - radiated Lw [dB(A)]	57,3
IP	X2	Sound power level exhaust inlet Lw [dB(A)]	43,6
Max ambient temperature for continuous operation (°C)	25	Sound power level supply outlet Lw [dB(A)]	60,2
Max Temperature of Exhaust Air (Continuous Operation)	40	Sound pressure level air extraction Lp [dB (A)] 3m - max speed	23,1
Min ambient temperature for continuous operation (°C)	0	Sound pressure level air supply Lp [dB (A)] 3m - max speed	39,7
Voltage (V)	230	Sound pressure level radiated Lp [dB (A)] 3m - max speed	36,8
Weight (Kg)	22		

Diametro Ø (mm)	150
Etichetta Energetica	NO
Size A (mm)	712
Size B (mm)	845
Size C (mm)	455
Size D (mm)	700
Size E (mm)	215
Size F (mm)	410
Size G (mm)	220

PER INFORMAZIONI:
 Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)
 Pre & Post Vendita: fax +39 02 90699302
 Email prevendita: prevendita@vortice-italy.com

Technical Data Sheet

CODE 12106

VORT HR 350 AVEL

Wall-mounting residential heat recovery unit



DESCRIPTION

ACCESSORIES



C TEMP
Code 12992

C SMOKE
Code 12993

CHCS
Code 12994

C PIR
Code 12998



PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com